



**QubicaAMF Worldwide, Inc.**  
8100 AMF Drive  
Mechanicsville, VA 23111  
866-460-QAMF (7263)

## MATERIAL SAFETY DATA SHEET: FULL DISCLOSURE

Medical Emergency Telephone INFOTRAC (352) 323-3500 or (800) 535-5053

### SECTION 1

PRODUCT IDENTITY: EasyBase™ (Activator) Bowling Lane Finish      DATE PREPARED: 2/6/07

MANUFACTURER'S CODE IDENTIFICATION: 294007051

NFPA/HMIS HAZARD CODES (minimal = 0; slight = 1; moderate = 2; serious = 3; severe = 4)  
Health: 1/2    Fire: 1/2    Reactivity: 0/0    Special/Personal Protection: /B

### SECTION 2

<u>INGREDIENTS:</u>	<u>CAS #</u>	<u>OSHA-PEL</u>	<u>ACGIH-TLV</u>	<u>% BY WT.</u>
Wax	Proprietary	None Est.	None Est.	21.0
Methylene Bis Phenylisocyanate	101-68-8	None Est.	None Est.	30.0
1-Methoxy, 2-Propanol Acetate	106-65-6	None Est.	None Est.	30.0
1-Pseudocumene	95-63-6	25	25	19.0

### SECTION 3 - Physical / Chemical Characteristics

BOILING POINT: 168-597°F	SPECIFIC GRAVITY: 1.03
VAPOR PRESSURE: Not applicable	PERCENT VOLATILE:
VAPOR DENSITY (AIR = 1): >1	EVAPORATION RATE: Slower than Diethyl Ether
SOLUBILITY IN WATER:	pH: Not applicable
APPEARANCE AND ODOR: Liquid, solvent	VOC: 3.1 lb/gal

### SECTION 4 - Fire and Explosion Hazard Data

FLASH POINT: 108°F. SFCC  
FLAMMABLE LIMITS: Combustible Class 2  
EXTINGUISHING MEDIA: Carbon dioxide, dry chemical or foam.  
SPECIAL FIREFIGHTING PROCEDURES: Firefighters and others exposed to vapors or products of combustion should wear self-contained breathing apparatus.  
UNUSUAL FIRE AND EXPLOSION HAZARDS: Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Closed container may explode when exposed to extreme heat. Never use welding or cutting torch on or near container (even empty) because product may ignite explosively. Heavier-than-air vapors can travel long distances to ignition sources and flash back. Firefighters should use self-contained breathing apparatus with face piece.

### SECTION 5 - Reactivity Data

STABILITY: Stable  
HAZARDOUS POLYMERIZATION: Will not occur  
INCOMPATIBILITY: This material is incompatible with strong oxidizing agents, strong mineral acids, alkali metals and halogens.  
HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of carbon, oxides of nitrogen and possibly hydrogen cyanide fumes.

FM-0279

**MATERIAL SAFETY DATA SHEET**  
**EasyBase™ (Activator) Bowling Lane Finish**  
Page 2 of 3

**SECTION 6 – Health Hazard Data**

ROUTES OF ENTRY/SIGNS AND SYMPTOMS OF EXPOSURE: **Inhalation:** Inhalation of vapors (especially if sprayed or heated).

EFFECTS OF OVEREXPOSURE: **Acute:** Inhalation: May cause allergic respiratory reaction. Effects may be permanent. Ingestion: May cause severe gastrointestinal irritation and possible corrosive action in the mouth, stomach tissue and digestive tract. Eyes: This material may cause eye irritation, redness and blurred vision. **Chronic:** Repeated excessive exposure may cause chronic, adverse systemic effects. This material is considered a sensitizer that may cause a portion of exposed people to develop an allergic skin or respiratory reaction in normal tissue after repeated exposure.

CARCINOGENS: This product contains no reported carcinogens or suspected carcinogens.

EMERGENCY AND FIRST AID PROCEDURES: **Eyes:** Flush with large quantities of lukewarm water for 15 minutes and seek medical attention. **Skin:** Do not remove with solvent. Use waterless hand cleaner followed by soap and water. Remove and clean contaminated clothing. **Inhalation:** Remove to fresh air. Aid breathing as needed. Call a physician. **Ingestion:** Rinse mouth. Call a physician or Poison Control Center immediately. DO NOT induce vomiting unless advised by a physician.

**SECTION 7: Precautions For Safe Handling And Use**

SPILL OR LEAK PROCEDURES: **Small Spills:** Absorb spill with suitable absorbent material and place in a closed container. **Large Spills:** Dike area and pump into closed containers. Prevent this material from entering waterways. Ventilate area and wear protective equipment during cleanup.

WASTE DISPOSAL METHOD: At this time, this material or its containers would not be considered hazardous wastes as defined under the federal RCRA regulations (40 CFR 261) if discarded. Care should be taken to ensure that the material or its containers are disposed of in an approved facility in accordance with current federal, state, and local regulations.

HANDLING AND STORING: Store indoors. Keep product containers cool, dry and away from sources of ignition. Use and store this product with adequate ventilation. DO NOT smoke in storage areas or while handling this product.

OTHER PRECAUTIONS: Keep out of reach of children.

**MATERIAL SAFETY DATA SHEET**  
**EasyBase™ (Activator) Bowling Lane Finish**  
Page 3 of 3

**SECTION 8: Control Measures**

**VENTILATION:** Use ventilation as required to control vapor concentrations. Avoid prolonged or repeated breathing of vapors. If exposure exceeds TLV, use a NIOSH-approved respirator to prevent overexposure.

**RESPIRATORY PROTECTION:** Prevent any person from breathing vapors or mists. Unless air monitoring establishes exposure limits below TLV, NIOSH approved respiratory equipment must be used. Adequate ventilation achieved by fresh air movement is necessary during the application of this material.

**GLOVES:** Chemical-resistant gloves and skin cream and/or protective clothing.

**EYE PROTECTION:** Wear face shield or chemical goggles.

**OTHER PROTECTIVE EQUIPMENT:** Wear protective clothing to prevent skin contact. Eye wash station and safety shower should be available.

**WORK/HYGIENIC PRACTICES:** Do not smoke in storage areas or when handling this product.

**SECTION 9: Transport Information**

D.O.T. Shipping Name:	Paint
D.O.T. Hazard Class	Flammable Liquid
D.O.T. Label:	
U.N. Number:	U.N. 1263
Bill of Lading:	Paint, Flammable Liquid, U.N. 1263, PGII

Health and safety information presented on this form is generally applicable at recommended dilutions, varying only in degree.

This information was compiled from current, reliable sources and is believed to be correct. As data, and/or regulations change, and conditions of use and handling are beyond our control, no warranty, express or implied, is made as to completeness or continuing accuracy of this information.

[Back](#)